

NITROGEN PROJECT FORM



Customer Information:

Customer: _____ Project Name: _____

Address: _____ Company: _____

State: _____ City: _____

Phone: _____ Zip: _____

Email: _____

Systems Information (circle one):

Building: New Existing

Fire Sprinkler Condition - Leak Rate:

All Potter IntelliGen Nitrogen Generator sizes assume a leak rate of less than 6 PSI per 24 hours. If leak rate is known or if other requirements are needed, please note below:

 _____ PSI per 24 Hours

System: Dry Pre-action

System Material: Steel Galvanized

Model/Manufacturer of Dry Valve: _____

Standard Nitrogen Purity Level 98%

Individual Riser Information:

Riser #	Capacity (Gallons)	Supervisory Pressure (PSI)
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		

Electric Requirements (circle one):

Voltage: 120v 208v 230v 460v

Phase: Single Three

Purge Valves (select):

Check one Purge Valve option. One required for each riser. More than one may be selected for quoting purposes.

Nitrogen Purge Valve (NGP-SPV)

IntelliPurge Nitrogen Purge Valve (INS-PV)

IntelliPurge Remote Annunciator (INS-RA)
(Optional with INS-PV)

Nitrogen Generator Accessories (select):

Air Maintenance Device (AMD-1)
(One required for each riser)

Nitrogen Generator Replacement Filter Kit

Bleeder Valve for Testing Purposes (BVL)

Distributor Information:

Salesperson: _____ Company: _____ Location: _____

Email: _____ Phone: _____ Date: _____

Return to Potter Electric Signal Company by email: corrosion@pottersignal.com or Fax: 800-768-8377